











## **BOTTOM ENTRY ANGLE BOX IP66/68**







## **Features and Benefits**

- Bottom Entry Angle Box for industrial lighting applications
- This new design allows the terminals to sit proud of the box for more efficient and easier termination of cables
- Screw on lid provides ease of installation. Lid locking with a special key prevents unauthorized tampering
- Supplied complete with lanyard for securing lid
- Only approved CCG cable glands and Ex e terminals must be used
- Din Rail mounting studs are provided for use with terminal blocks
- Dust and watertight to IP66/68, when fitted with CCG sealed cable glands
- Threaded entries complete with blanking plugs. No drilling of the cable entries required
- Internal earthing to all entries and rail
- Various sized terminals and configurations available
- 3 x Blanking plugs are provided with each Angle Box

## **Technical Data**

Sizes Available - Available in 3 sizes, M20, M25 or M32 thread entries

Box Material – Impact, corrosion and UV resistant glass reinforced polyester compound

Seal Material — Low Temp. Nitrile Rubber

Inserts — Brass, internal earth continuity ring and earth stud provided

Optional Accessories - Certified Terminals, Box Spanner (Lid Locking Key)









For further details please contact

Mark Jansz

Business Development Manager – Mining

Phone – 0438128583, Email – mark.jansz@mmem.com.au

